SITE ACCEPTABILITY STANDARDS—Continued

	Day-night average sound level (in decibels)	Special approvals and requirements
Unacceptable	Above 75 dB	Special Approvals (2). Environmental Review (3). Attenuation (5).

[44 FR 40861, July 12, 1979, as amended at 49 FR 12214, Mar. 29, 1984]

§51.104 Special requirements.

(a)(1) Noise attenuation. Noise attenuation measures are those required in addition to attenuation provided by buildings as commonly constructed in the area, and requiring open windows for ventilation. Measures that reduce external noise at a site shall be used wherever practicable in preference to the incorporation of additional noise attenuation in buildings. Building designs and construction techniques that provide more noise attenuation than typical construction may be employed also to meet the noise attenuation requirements.

(2) Normally unacceptable noise zones and unacceptable noise zones. Approvals in Normally Unacceptable Noise Zones require a minimum of 5 decibels additional sound attenuation for buildings having noise-sensitive uses if the daynight average sound level is greater than 65 decibels but does not exceed 70 decibels, or a minimum of 10 decibels of additional sound attenuation if the day-night average sound level is greater than 70 decibels but does not exceed 75 decibels. Noise attenuation measures in Unacceptable Noise Zones require the approval of the Assistant Secretary for Community Planning and Development, or the Certifying Officer for activities subject to 24 CFR part 58. (See §51.104(b)(2).)

(b) Environmental review requirements. Environmental reviews shall be conducted pursuant to the requirements of 24 CFR parts 50 and 58, as applicable, or other environmental regulations issued by the Department. These requirements are hereby modified for all projects proposed in the Normally Unacceptable and Unacceptable noise exposure zones as follows:

(1) Normally unacceptable noise zone. (i) All projects located in the Normally Unacceptable Noise Zone require a Special Environmental Clearance except an EIS is required for a proposed project located in a largely undeveloped area, or where the HUD action is likely to encourage the establishment of incompatible land use in this noise zone.

(ii) When an EIS is required, the concurrence of the Program Assistant Secretary is also required before a project can be approved. For the purposes of this paragraph, an area will be considered as largely undeveloped unless the area within a 2-mile radius of the project boundary is more than 50 percent developed for urban uses and infrastructure (particularly water and sewers) is available and has capacity to serve the project.

(iii) All other projects in the Normally Unacceptable zone require a Special Environmental Clearance, except where an EIS is required for other reasons pursuant to HUD environmental policies.

(2) Unacceptable noise zone. An EIS is required prior to the approval of projects with unacceptable noise exposure. Projects in or partially in an Unacceptable Noise Zone shall be submitted to the Assistant Secretary for Community Planning and Development, or the Certifying Officer for activities subject to 24 CFR part 58, for approval. The Assistant Secretary or the Certifying Officer may waive the EIS requirement in cases where noise is the only environmental issue and no outdoor noise sensitive activity will take place on the site. In such cases, an environmental review shall be made

Notes: (1) Acceptable threshold may be shifted to 70 dB in special circumstances pursuant to §51.105(a).
(2) See §51.104(b) for requirements.
(3) See §51.104(b) for requirements.
(4) 5 dB additional attenuation required for sites above 65 dB but not exceeding 70 dB and 10 dB additional attenuation required for sites above 70 dB but not exceeding 75 dB. (See §51.104(a).)
(5) Attenuation measures to be submitted to the Assistant Secretary for CPD for approval on a case-by-case basis.

§51.105

pursuant to the requirements of 24 CFR parts 50 or 58, as appropriate.

[44 FR 40861, July 12, 1979, as amended at 61 FR 13333, Mar. 26, 1996]

§51.105 Exceptions.

- (a) Flexibility for non-acoustic benefits. Where it is determined that program objectives cannot be achieved on sites meeting the acceptability standard of 65 decibels, the Acceptable Zone may be shifted to $L_{\rm dn}$ 70 on a case-by-case basis if all the following conditions are satisfied:
- (1) The project does not require an Environmental Impact Statement under provisions of §51.104(b)(1) and noise is the only environmental issue.
- (2) The project has received a Special Environmental Clearance and has received the concurrence of the Environmental Clearance Officer.
- (3) The project meets other program goals to provide housing in proximity to employment, public facilities and transportation.
- (4) The project is in conformance with local goals and maintains the character of the neighborhood.
- (5) The project sponsor has set forth reasons, acceptable to HUD, as to why the noise attenuation measures that would normally be required for new construction in the L_{dn} 65 to L_{dn} 70 zone cannot be met.
- (6) Other sites which are not exposed to noise above $L_{\rm dn}$ 65 and which meet program objectives are generally not available.

The above factors shall be documented and made part of the project file.

 $[44\ {\rm FR}\ 40861,\ {\rm July}\ 12,\ 1979,\ {\rm as\ amended}\ {\rm at}\ 61\ {\rm FR}\ 13334,\ {\rm Mar.}\ 26,\ 1996]$

§51.106 Implementation.

- (a) Use of available data. HUD field staff shall make maximum use of noise data prepared by others when such data are determined to be current and adequately projected into the future and are in terms of the following:
- (1) Sites in the vicinity of airports. The noise environment around airports is described sometimes in terms of Noise Exposure Forecasts, abbreviated as NEF or, in the State of California, as Community Noise Equivalent Level, abbreviated as CNEL. The noise envi-

ronment for sites in the vicinity of airports for which day-night average sound level data are not available may be evaluated from NEF or CNEL analyses using the following conversions to DNL:

DNL≈NEF+35 DNL≈CNEL

(2) Sites in the vicinity of highways. Highway projects receiving Federal aid are subject to noise analyses under the procedures of the Federal Highway Administration. Where such analyses are available they may be used to assess sites subject to the requirements of this standard. The Federal Highway Administration employs two alternate sound level descriptors: (i) The Aweighted sound level not exceeded more than 10 percent of the time for the highway design hour traffic flow, symbolized as L_{10} ; or (ii) the equivalent sound level for the design hour, symbolized as L_{eq} . The day-night average sound level may be estimated from the design hour $L_{\rm 10}$ or $L_{\rm eq}$ values by the following lowing relationships, provided heavy trucks do not exceed 10 percent of the total traffic flow in vehicles per 24 hours and the traffic flow between 10 p.m. and 7 a.m. does not exceed 15 percent of the average daily traffic flow in vehicles per 24 hours:

 $\begin{array}{l} DNL{\approx}L_{10} \; (design \; hour){\longrightarrow} 3 \; decibels \\ DNL{\approx}L_{eq} \; (design \; hour) \; decibels \end{array}$

Where the auto/truck mix and time of day relationships as stated in this section do not exist, the HUD Noise Assessment Guidelines or other noise analysis shall be used.

(3) Sites in the vicinity of installations producing loud impulsive sounds. Certain Department of Defense installations produce loud impulsive sounds from artillery firing and bombing practice ranges. Noise analyses for these facilities sometimes encompass sites that may be subject to the requirements of this standard. Where such analyses are available they may be used on an interim basis to establish the acceptability of sites under this standard. The Department of Defense uses daynight average sound level based on Cweighted sound level, symbolized L_{Cdn}, for the analysis of loud impulsive